



Holder of Certificate: Flokk Sp.z.o.o.

Gornicza 8 62-700 Turek POLAND

**Certification Mark:** 





Product: Swivel Chairs

for a user weight of up to 150 kg

Tested according to: PPP 51960C:2021

DIN EN 1335-1:2020 DIN EN 1335-2:2019 DIN 4573:2021 AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713225280

**Valid until:** 2026-11-16

**Date**, 2021-11-18

( Jens Biesenack )



ш

7



## CERTIFICATE

No. Z1A 090658 0080 Rev. 00

Model(s): ACTION

## Parameters:

Seat support	Synchronous mechanism, synchronous movement adjustable by means of adjustment. Seat depth and seat tilt adjustment. Back inclination can be locked in locking steps
Height adjustment	Seat height adjustment by means of gas pressure spring.  Manufacture KGS, type STKM 12, class 4
Seat surface	Plastic seat shell, upholstered seat.
Backrest	Backrest frame made of plastic and aluminium, mesh backrest surface with textile cover, lumbar support with hight adjustment. The height of the backrest is not adjustable.
Armrests	Plastic armrests, the armrests are adjustable in the hight, the pads forwards and backwards
Base	Aluminium base, Ø 721 mm
Castors	Load-dependent braked double castors Ø 65 mm, type "H" for soft floors

